

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

**CORRECTED VERSION**

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date  
24 December 2003 (24.12.2003)

PCT

(10) International Publication Number  
**WO 2003/106108 A1**

(51) International Patent Classification: B24B 49/04, 5/42

(74) Common Representative: MARPOSS SOCIETÀ PER AZIONI; Patent Department, via Saliceto 13, I-40010 Bentivoglio Bo (IT).

(21) International Application Number:

PCT/EP2003/005740

(22) International Filing Date: 2 June 2003 (02.06.2003)

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language:

English

(26) Publication Language:


English

(30) Priority Data:

BO2002A000369 12 June 2002 (12.06.2002) IT

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).(71) Applicant (*for all designated States except US*): MARPOSS SOCIETÀ PER AZIONI [IT/IT]; via Saliceto 13, I-40010 Bentivoglio (IT).**Published:**— *with international search report**[Continued on next page]*

---

(54) Title: APPARATUS FOR CHECKING THE DIMENSIONAL AND GEOMETRIC FEATURES OF PINS

WO 2003/106108 A1

(57) Abstract: An apparatus for checking diameter and roundness of crankpins (42) in the course of the machining in a grinding machine, includes a Vee-shaped reference device (70), a gauging device with a movable feeler (67) associated with the Vee-shaped device (70) and a movable support (5, 40, 41, 60) device for the Vee-shaped reference device. The movable support device is coupled (5) to the grinding-wheel slide (1) and includes, in working condition, two parallelogram structures (40, 41) in series enabling substantially translation displacements of the Vee-shaped device (70). One of the two parallelogram structures (40, 41) includes an axially movable stem (32), with end surfaces (38, 39) that, in working condition, contact the external surface of bearings (15, 19), thereby setting the distance separating two of the four vertexes (11, 7, 14, 18) of the parallelogram (40), whereas when the apparatus is in the rest position, at least one of said end surfaces (38, 39) is separated from the surface of the associated bearing. During the checking, the direction of the feeler (67) displacements remains substantially unaltered.



(48) Date of publication of this corrected version:

10 June 2004

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(15) Information about Correction:

see PCT Gazette No. 24/2004 of 10 June 2004, Section II